

# LIBERTY™ SBS Self-Adhering Cap Sheet

Granule-surfaced roofing membrane providing durable protection for residential low-slope areas



- Perfect for low-slope roofs such as on porches, garages, car ports, and sheds.
- Self-Adhering installation eliminates open flames, hot asphalt, or dangerous chemicals on your roof.

# LIBERTY™ SBS Self-Adhering Cap Sheet



## Description:

LIBERTY™ SBS Self-Adhering Cap Sheet is a durable modified bitumen granule-surfaced membrane designed and manufactured to meet relevant industry and code requirements. The product is designed for use as a waterproofing membrane and is reinforced with a polyester mat coated with polymer-modified asphalt.

## Uses:

LIBERTY™ SBS Self-Adhering Cap Sheet is designed to be used with LIBERTY™ SBS Self-Adhering Base/Ply Sheet to help protect low-slope areas (1/2:12 - 3:12) of your roof.

## Advantages:

- LIBERTY™ systems are applied without torches, open flames, hot asphalt, or messy solvent-based adhesives and are suitable for primed plywood decks and other substrates.
- Available in seven colors to help complement popular Timberline® and other GAF asphalt shingle colors.
- Up to 20-Year Limited Warranty against manufacturing defects available, depending on systems.<sup>1</sup>

## Application:

LIBERTY™ SBS Self-Adhering Cap Sheet is applied to approved substrates using its unique self-adhering formulation. Technical and sales information can be obtained through Technical Services at 877-GAF-ROOF.

## This product meets or exceeds the following ASTM D6164 - Type I, Grade G, minimum requirements:

Properties	Test Method	Value
Tensile Strength @ 0°F (min), lbf/in.	ASTM D5147	70
Elongation @ 0°F (nom.), %	ASTM D5147	20
Low-Temperature Flexibility (max), °F	ASTM D5147	0
Tear Strength (min.), lbf	ASTM D5147	55
Dimensional stability, (max) %	ASTM D5147	1

**Note:** Values stated are approximate and subject to normal manufacturing variation. These values are not guaranteed and are provided solely as a guide. GAF reserves the right to change or modify, at its discretion, any of the information, requirements, specifications, or policies contained in this document.

## Application Standards:

<ul style="list-style-type: none"> <li>UL Listed to ANSI/UL790<sup>3</sup>, Class C</li> </ul>	
<ul style="list-style-type: none"> <li>FM Approved<sup>4</sup></li> </ul>	
<ul style="list-style-type: none"> <li>Miami-Dade County Product Control approved</li> </ul>	
<ul style="list-style-type: none"> <li>State of Florida Approved</li> </ul>	
<ul style="list-style-type: none"> <li>Texas Dept. of Insurance Report RC-121</li> </ul>	
<ul style="list-style-type: none"> <li>ASTM D6164 - Type I, Grade G</li> </ul>	

## Product Details:

Roll size	1 square — excludes laps <sup>2</sup> (1111.6 gross sq. ft.) (10.4 m <sup>2</sup> )
Roll length	34.0' (10.4 m)
Roll width	39.375" (1.0 m)
Aprox. roll weight	96.4 lb. (43.7 kg)
Product thickness	0.157" (4 mm.)

<sup>1</sup> Exclusions apply. See *Limited Warranty on LIBERTY™ SBS Self-Adhering Materials* for complete coverage and restrictions.

<sup>2</sup> Installed coverage will be lower and depend on quantity and width of side and end laps.

<sup>3</sup> Refer to UL Product iQ for actual assemblies.

<sup>4</sup> Refer to FM RoofNav.com for actual assemblies.

Visit [gaf.com/Liberty](https://gaf.com/Liberty)  
or Call **877-GAF-ROOF**

We protect what matters most™

